



دروفايل ٢ مم (٥٦٥٥)

طلاء مانى مكون من مستحلب الاكريليك مع حبيبات رخامية يتسم بالقوة والمتانة يتوفر بتشكيلة الوان جميلة ومتناسقة تعطى مظهر ديكورى رائع

الوصف

– مقاوم لعوامل الجويه وعوامل التعريه
– يتسم بالمتانة والقوة ومرونة عالية – سهولة بالتنفيذ و سهولة اختيار اللون
– مقاوم للماء وقابل للغسيل – مقاوم للاحتكاك

الخصائص

- يستخدم للتطبيقات الخارجية والداخلية على جميع انواع الاسطح الخرسانية والاسمنتية على ان يكون السطح جافا تماما ونظيفا من الشوائب والأتربة
- يتم مد طبقة من اوسكار دروفيل بالمسطرين المعدني ثم تخشن عاموديا او افقيا بالمسطرين البلاستيكية للحصول على الشكل المطلوب.

طريقة الاستخدام

المسطرين المعدني
المسطرين البلاستيكي

طريقة التنفيذ

8 - 10 م ٢ للبرميل ٣٠ ك حسب طبيعة السطح.








معدل الانتشار







برميل ٣٠ ك





العبوة



OSCAR DRAWFILE 2MM 5655

Product Description	High Quality Graffiato Texture paint made of co-polymer emulsion. It can be used for interior and exterior application. It shows better weather stability. It gives textured finish with line pattern. The grooves gives good aesthetic appearance to the textured surface. The application is by trowel and it is easy to apply.	 Interior/Exterior
Recommended Uses	- This product is designed for decoration of interior and exterior surfaces.	 Water Based
Substrate	-Cement plaster, concrete, block work, rendered surfaces, gypsum board etc. Substrate should be sound and any defects in the substrate like surface undulations, cracks, pin holes etc. should be rectified/filled before starting the painting.	 Volume Solid 72 ± 2%
Special Features	<ul style="list-style-type: none"> • Good weather durability • Coarse textured finish • Better coverage and spread rate • Easy to apply • Grooves gives better finish • Better adhesion on wall substrate 	 Coverage: 2.5-3.0 kg/m ²
Product test standards	<p>Specific Gravity:</p> <p>ASTM D 1475 / BS EN ISO 2811-1 : 2016</p> <p>Gloss:</p> <p>ASTM D 523 / BS EN ISO 2813 : 2014</p> <p>Volume Solids:</p> <p>ASTM D 2697 / BS EN ISO 3233-3 : 2015</p> <p>Viscosity:</p> <p>ASTM D 562</p>	 Trowel  Trowel  Scraper
Packing	<p>30 KG</p> <p>25 KG</p>	

Storage	Store in cool and well ventilated place protected from heat and direct sunlight. Containers must be kept tightly closed.	 VOC - 20 g/L
Flash Point	Not Applicable	
Physical Properties		Surface Drying: 2Hours @30°C
Finish	Texture-Matt	
Colors	White and assorted colors	
Specific Gravity	1.78+/-0.02	
Volume Solids	72 ± 2 % ; Approximately 84% Solid by weight	
Thinner & Cleaner	Water	
Dilution	Maximum 2-3%	
Mixing Ratio	Not Applicable	
Pot Life	Not Applicable	
Shelf Life	24 month when stored in original sealed container In a cool dry place	 Hard Drying: 24 hours @ 30° C
Wet Film Thickness	1110-2780 μ	
Dry Film Thickness	800-2000 μ per each coat	
Theoretical Coverage	0.36-0.9 m2/L per each coat/ 2.5-3.0 Kg/m2 Spreading rate depends on applied film thickness, surface imperfections, type of surface texture, porosity of the substrate, environment temperature and wastage during application. Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.	 25KG
Surface Dry	2 hour at 30° C	
Over Coat	24 hours	
Hard dry	24 hours at 30° C	 30KG
Surface Preparation	The surface to be coated should be clean, non-chalky, dry and free from loose material, dust etc. In case of need sanding required to remove loose particles from the surface.	
Recommended Coating System	Stir the contents well before use. Do not apply the paint in very cold conditions, to impervious surfaces or surfaces subject to steam and condensation. It is advisable to build up coat thickness by applying in thin layers, instead of applying one single thick coat to avoid cracking Avoid painting below 10° C and humidity more than 85% .	 Non-Flammable

<p><u>Exterior</u></p> <p>Primer</p> <p>Top Coat</p>	<p>We can apply directly on concrete without primer</p> <p>1 X Oscar Original Sealer 5290</p> <p>1 X Oscar Drawfile 2.0MM 5655</p>	 <p>Paint System</p>
<p><u>Interior</u></p> <p>Primer</p> <p>Top Coat</p>	<p>1 X Oscar Beauty Sealer 5292</p> <p>1 X Oscar Drawfile 2.0MM 5655</p>	
<p><u>Repainting System</u></p> <p>Substrate</p> <p>Primer</p> <p>Top Coat</p>	<p><i>For repainting & fresh substrate same procedure as below</i></p> <p>Any smooth existing surfaces</p> <p>1 X Oscar Original Sealer 5290/Oscar Beauty Sealer 5292</p> <p>1 X Oscar Drawfile 2.0MM 5655</p>	 <p>Splashes on eye-wash with Water</p>
<p><u>Application Data</u></p>	<p>Application by Trowell</p> <p>Apply the Drawfile 2.0MM by using Trowel and scrapper</p> <p>Design the groves using plastic Trowel/wood trowel</p> <p>The rough surface of Plastic/Wood trowel helps for creating grooves and textured surface</p>	 <p>Splashes on Skin-wash with soap & hot water</p>
<p><u>Health and Safety</u></p>	<p>Ensure good ventilation during application and drying.</p> <p>Avoid contact of the product with skin and eyes by using proper gloves, apron , goggles and mask.</p> <p>If splashes enter eyes wash with plenty of water.</p> <p>Keep out of reach of children.</p> <p>Remove splashes from skin with soap and warm water.</p> <p>In case of insufficient ventilation during spraying, wear suitable respiratory equipment.</p> <p>Do not breathe vapour / spray.</p>	
<p><u>DISCLAIMER</u></p>	<p>The above information is based on internal testing and our accumulated experience. This information is given in good faith but without warranty as the conditions under which the product is used are often beyond our control. This data sheet supersedes those previously issued and may be changed without prior notice.</p>	 <p>Disclaimer</p>